

# Interfilm®

---

IMPORTS AND WHOLESALE OF SELF-ADHESIVE TAPES  
LILOGLOU ARISTOTELIS GEORGE  
ZAKINTHOU 13, PIRAEUS  
PHONE NO.: (+30)210-4118538  
Email : [interfilmcompany@gmail.com](mailto:interfilmcompany@gmail.com)  
Web site: [www.interfilm.gr](http://www.interfilm.gr)

Piraeus, November 2019

## Technical Data Sheet

Product: **Anti Slip Tapes**



### **Product description:**

INTERFILM Anti Slip tapes use PVC backing material with sandy surface, combines with a high performance solvent acrylic adhesive, protected by an easy-release silicon release paper.

### **Properties**

Color	Black, White, Transparent, Yellow-Black
Release paper	Glassine paper
Backing	PVC film
Adhesive	Solvent Acrylic
Total Thickness	0.70±0.01mm
Tack	≥5#
Tensile strength	≥50 N/inch
180° Peel adhesion	≥6 N/inch
Applying Temperature	+10~40°

**Important note:**

1. The data above are typical values only and should not be used for specifications purpose.
2. Tolerance: Weight and Thickness:  $\pm 10\%$ . Width:  $\pm 3\text{mm}$ , Length: Cut, Roll:  $\pm 0.3\text{m}$ .

**Storage & Shelf life:**

12 months when stored at 21 (70/50%) relative humidity out of direct sunshine.

**Surface preparation:**

It is essential, as all pressure-sensitive tapes, that the surface to which the tape is applied must be clean, dry, free of grease, oil or other contaminants.

**Product use:**

It essential that the user evaluate the INTERFILM product to determine whether it is fit for a particular purpose and user's method of application. Good results will be obtained when applied to a clean, dry surface with a suitable pressure on INTERFILM products between  $+10\sim+40$  ( $+50\sim+150$ ).

**Features:**

1. Strong solvent acrylic adhesive
2. Water, temperature, UV resistance
3. Outdoor and indoor use

**Typical application:**

Stairs, swimming places, bathrooms, warehouses ect for general anti slip purpose.