

Saratoga High Temperature Silicone Sealant Technical Data Sheet

Saratoga High Temperature Silicone Sealant is an acetic one-component silicone sealant that cures quickly thanks to the atmospheric humidity, forming extremely elastic and resistant seals. It is pure silicone and does not contain solvents.

APPLICATION FIELDS

Ideal for ovens, boilers, heaters, heating and air-conditioning systems, pipes for hot fluids transport, and appliances (electric irons, ovens, etc).

Suitable for uses between -60 and +280°C, with peaks of up to +380°C. High resistance to UV rays and atmospheric agents. Excellent adhesion to glass, ceramic, steel, aluminium, some plastic materials (except PE, PP, PTFE), wood and varnished supports.

APPLICATION

- All surfaces must be dust free, clean, compact, dry and degreased. Prepare the surface for sealing, placing a masking tape, such as Saratoga Vernimask, on both sides of the joint (remove right after application).
- Cut the nozzle at the desired diameter.
- Cannot be painted, therefore, if necessary paint before applying.
- Apply using a standard sealant gun.
- Smooth the sealant down within 10 minutes with a spatula wetted with soap and water.
- Clean within 10 minutes with a clean cloth wetted with solvent or Saratoga VIA • SIL. When cured, clean with Saratoga VIA • SIL Indurito.

STORAGE AND SHELF LIFE

In unopened original packaging, between +20 and +25°C its shelf life is 24 months since manufacturing date.

Specific data		
Kind of sealant		Acetic silicone sealant
Colour		Red
Specific weight		1,04
Consistency		Thixotropic
Extrusion rate	g/m	50-70
Working time	minutes*	5
Cure time	mm/24h*	3
Application temperature	°C	+5/+40
Working movement	%	20
Heat resistance	°C	-60/+280
Heat resistance (peaks)	°C	380

*At 23°C and 50% relative humidity

CAUTIONS

Keep out of the reach of children.

Consult Material Safety Data Sheet for full list of hazards and the directions on the product label itself.

For further information, please visit our site www.saratoga.it

Product Description	Pack size	Product code	Box quantity
High Temperature Silicone Sealant cartridge	280ml	85 134 003	15



Rev 01 del 19/04/2016- The technical data contained herein is based on our present knowledge and experience and we cannot be held liable for any errors, inaccuracies, omissions or editorial failings . All the information herein do not involve the assumption of responsibility in case of damages. Before using the product, the user should carry out any necessary test in order to ensure that the product is suitable for the intended application. All users should contact the seller or the manufacturer of the product for additional technical information concerning its use if they think that the information in their possession needs to be clarified in any way, for specific features, please contact Saratoga Int Storza spa. Our specialists are at your disposal for further information.